

Data sheet PM 007 (007-1AB10)

Technical data

Order no.	007-1AB10
------------------	------------------

Type	PM 007
------	--------

Module ID	-
-----------	---

General information

Note	-
------	---

Features	Output supply Power supply DC 24 V, 4 A Power supply DC 24 V for bus supply 5 V, 2 A Reverse polarity protection Overvoltage protection Module supply
----------	--

Technical data power supply

Input voltage (rated value)	DC 24 V
-----------------------------	---------

Input voltage (permitted range)	DC 20.4...28.8 V
---------------------------------	------------------

I_{t}	-
----------------	---

Current consumption (no-load operation)	-
---	---

Current consumption (rated value)	0.5 A
-----------------------------------	-------

Max. current drain at backplane bus	2 A
-------------------------------------	-----

Max. current consumption load supply	4 A
--------------------------------------	-----

Max. current drain load supply	4 A
--------------------------------	-----

Short-circuit protection	yes
--------------------------	-----

Efficiency	89 %
------------	------

Power loss	1.4 W
------------	-------

Overvoltage protection	36 V
------------------------	------

Status information, alarms, diagnostics

Status display	yes
----------------	-----

Interrupts	no
------------	----

Process alarm	no
---------------	----

Diagnostic interrupt	no
----------------------	----

Diagnostic functions	no
----------------------	----

Diagnostics information read-out	none
----------------------------------	------

Supply voltage display	green LED
------------------------	-----------

Group error display	red LED
---------------------	---------

Channel error display	none
-----------------------	------

Housing

Material	PPE / PPE GF10
----------	----------------

Mounting	Profile rail 35 mm
----------	--------------------

Mechanical data

Dimensions (WxHxD)	12.9 mm x 109 mm x 76.5 mm
--------------------	----------------------------

Net weight	74 g
------------	------

Weight including accessories	74 g
------------------------------	------

Gross weight	89 g
--------------	------

Environmental conditions

Operating temperature	0 °C to 60 °C
-----------------------	---------------

Storage temperature -25 °C to 70 °C

Certifications

UL certification yes

KC certification yes