

System SLIO CPU variants 014-CEF0x31



- The System SLIO CPU variants 014-CEF0x31 are identical to the basic CPU 014-CEF0R01.
- They differ only in the activation of the features mentioned below, all other data correspond to those of the basic CPU 014-CEF0R01.
- Information on the structure and configuration can be found in the manual of the basic CPU 014-CEF0R01.
<https://www.yaskawa.co.uk/services/download-center>

Features

CPUs	Work memory		PROFIBUS	
	128kByte	256kByte	DP-Slave	DP-Master
Basis CPU				
014-CEF0R01	X	optional	optional	optional
CPU variants				
014-CEF0R31	-	X	-	-
014-CEF0S31	-	X	X	-
014-CEF0M31	-	X	X	X

Properties

Basis CPU 014-CEF0R01
HW: 02 | CPU-FW: V3.0.9

- SPEED7 technology integrated
- Programmable via SPEED7 Studio, Siemens SIMATIC Manager or Siemens TIA Portal
- Work memory 128kbyte integrated
(optionally expandable up to max. 256kByte by VSC)
- 256kbyte load memory integrated
- Slot for external storage media (lockable)
- Status LEDs for operating state and diagnostics
- X1/X4: Ethernet PG/OP channel for active and passive communication integrated
- X2: PtP(MPI) interface: Serial integrated interface for PtP communication with the protocols: ASCII, STX/ETX , USS, 3964(R), MODBUS RTU, master/slave switch able to MPI communication
- X3: MPI(PB) interface: MPI interface
(optional unlockable PROFIBUS DP master / slave functionality by VSC)
- PROFINET IO controller and I-Device via Ethernet PG/OP channel
- OPC UA project via Ethernet PG/OP channel
- WebVisu project via Ethernet PG/OP channel
- Up to 64 SLIO modules placeable
- I/O address area digital/analog 2048byte
- 512 timer/counter, 8192 flag byte